

KombiSIGN 70 / Audible Devices 844

# Siren element alternating 24VDC BK



|           |              |
|-----------|--------------|
| Part No.: | 844.123.55   |
| Series:   | KombiSIGN 70 |



## MECHANICAL DATA

|                             |              |
|-----------------------------|--------------|
| Height                      | 79 mm        |
| Diameter                    | 70 mm        |
| Materials                   | PC<br>PC/ABS |
| Housing colour              | Black        |
| Protection category         | IP40         |
| Working temperature minimum | -20°C        |
| Working temperature maximum | +50°C        |
| Weight with packaging       | 134 g        |
| Product weight              | 112 g        |

## ELECTRICAL DATA

|                             |                    |
|-----------------------------|--------------------|
| Operating voltage           | 24V                |
| Operating voltage type      | DC                 |
| Operating voltage tolerance | +/- 10%            |
| Rated operational voltage   | 24 VDC             |
| Rated operational current   | 100 mA             |
| Rated inrush current        | <10A               |
| Protection class            | Protection class 2 |
| Pollution degree            | 2                  |

## ACOUSTIC DATA

|                             |                  |
|-----------------------------|------------------|
| Volume (max) at 1m distance | 105,0 dB (A)     |
| Acoustic signal image       | Alternating tone |
| Acoustic service life       | 5,000 h minimum  |

## APPROVAL DATA

|                               |                       |
|-------------------------------|-----------------------|
| Conforms with CE              | Yes                   |
| Conforms with RoHS directive  | Yes                   |
| WEEE                          | Yes                   |
| Conforms with ATEX-directive  | No                    |
| Conforms with CCC             | No                    |
| Conforms with UL              | No                    |
| Conforms with FCC             | No                    |
| Conforms with IC              | No                    |
| EAC certificate available     | Yes                   |
| Conforms with UKCA (Importer) | Yes (WERMA (UK) Ltd.) |
| Conforms with CMIM            | No                    |
| Conforms with AS-I            | No                    |




For additional installation and mounting information, refer to the appropriate user guide at [www.werma.com](http://www.werma.com). This printed copy is for information only and is subject to alteration.

KombiSIGN 70 / Audible Devices 844

**Siren element alternating 24VDC BK**

|                       |    |
|-----------------------|----|
| ICAO Certification    | No |
| Conforms with DNV     | No |
| Conforms with RoHS CN | No |
| Conforms with VdS     | No |

**DRAWING**

For additional installation and mounting information, refer to the appropriate user guide at [www.werma.com](http://www.werma.com). This printed copy is for information only and is subject to alteration.